

951 KneeRX™ Heavy Duty



- Ergonomic benefit of 27 mm thickness designed for comfort and durability in extreme kneeling applications.
- The KneeRX™ Heavy Duty has a durable laminated heavy-duty rubber bottom surface for additional comfort and long-lasting wear in rough environments.
- For use on gravel, asphalt, concrete, dirty/oily surfaces, tile & wood flooring, metal grating, grass.
- Built-in handle easy to carry or hang up.
- Uni-Fusion™ lamination technology, engineered to resist in the harshest work environments.
- Resistant to most industrial fluids and chemicals.
- Silicone free material.
- Free of toxic DOP and DMF.

951 KneeRX™ Heavy Duty

PRODUCT SPECIFICATIONS		
Designation	Industrial Kneeling matting	
Type	Anti-fatigue	
Description	Heavy duty - Pebble top surface	
Material	Nitrile/PVC foam blend	
Process	Foaming and lamination, Uni-Fusion™ technology	
Category	Best	
Recommended use	Heavy duty – dry industrial environments - tool and maintenance carts and individual workstations	
Colours	Black	
Weight	0,4 kg and 0,8 kg	
Thickness	27 mm	
Standard sizes	20 cm x 38 cm 30 cm x 55 cm	
PRODUCT TESTING		
Tests	Norms	Results
Compression resistance @ 25%	ASTMD1056	6.0 – 12.0
Compression set	ASTM D1056	25% max.
Water absorption	ASTM D1667	0.1 lb/ft² max.
Tensile strength	ASTM D412	90 min.
Elongation	ASTM D412	100 min.
FIRE TESTING		
Flammability test	FMVSS #302	Pass
Sustainability	<ul style="list-style-type: none">• Recyclable material• Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals)	